



AGEPAN[®] THD INSTALL

THE ALTERNATIVE TO THE CONVENTIONAL
INSTALLATION LAYER

AGEPAN® THD INSTALL

ADVANTAGES

- Ideal as a quick-to-lay installation layer
- Gypsum boards can be fitted directly using approved screws and staples
- Direct attachment to OSB
- Quick integration of cable ducts
- Loads can be easily fixed to panel
- Saves working hours due to easy laying, no battens required
- "Solid" layer – no cavity
- F90-B (REI 90) constructions in AGEPAN® SYSTEM

AREAS OF APPLICATION

- Installation layer can be plastered directly with approved product (e.g. Rotkalk, Knauf Gips KG)
- Universal, pressure-resistant thermal insulation
- Clayboard systems with CLAYTEC®, Viersen
- Can be used as internal insulation in wall and roof areas
- Areas of application acc. to DIN 4108-10 table 13: DI-dm / DEO-ds / WI-dm /WTR

TECHNICAL DATA

PROPERTY	UNIT	VALUE		
Standard / Approval certificate		DIN EN 13171 / Z-23.15-1508		
Nominal thickness	mm	40	60	80*
Calculated dimension	mm	2650 x 600		
Coverage	mm	2650 x 600		
Approx. weight per m ²	kg / m ²	9,20	13,80	18,40
Edge design		Butt-edged		
Bulk density	kg / m ³	230		
Nominal thermal conductivity λ_D	W / (m*K)	0,047		
Rated thermal conductivity λ_R	W / (m*K)	0,050		
Water vapour diffusion resistance factor μ		3		
Water vapour diffusion equivalent air layer thickness s_d	m	0,12	0,18	0,24
Compressive strength	kPa	≥ 200		
Specific thermal capacity	J / (kg*K)	2100		
Formaldehyde emission class		E1 – formaldehyde-free glued		
Fire behaviour acc. to DIN EN 13501-1		E		
Building material class acc. to DIN 4102 B2		B2		
Hydrophobising group		WS 1,0		
Designation code		WF-EN 13171-T3-CS(10/Y)100-TR10-WS1,0	WF-EN 13171-T3-CS(10/Y)100-TR7,5-WS1,0	

* non-stock items

FUNKTIONSHILFEN



Your AGEPAN® SYSTEM partner

All the product names and company names used in this flyer are trade names and/ or registered trademarks belonging to the respective proprietors. Any reproduction requires the express authorisation of Sonae Arauco Deutschland GmbH and/ or the respective trademark proprietor. Sonae Arauco Deutschland GmbH assumes no liability for any possible errors in this prospectus. This flyer reflects the current technical specifications at the time of print and will be superseded by any new edition. It is applicable together with other documents of AGEPAN® SYSTEM. Our detailed instructions for use must be observed. The respective building regulations must be complied with. It is important to check the material's suitability for the intended purpose. Products with the PEFC® (Program for the Endorsement of Forest Certification Schemes) certificates can be delivered on demand and within availabilities. Version: January 2018